



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A61F 13/45	AI	(11) International Publication Number: WO 00/30585 (43) International Publication Date: 2 June 2000 (02.06.00)
<p>(21) International Application Number: PCT/SE99/02086</p> <p>(22) International Filing Date: 15 November 1999 (15.11.99)</p> <p>(30) Priority Data: 9803981-1 20 November 1998 (20.11.98) SE</p> <p>(71) Applicant (for all designated States except US): SCA HYGIENE PRODUCTS AB (SE/SE); S-405 03 Göteborg (SE).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): DREVIK, Solgun (SE/SE); Hulebacksvägen 16, S-435 35 Mölnlycke (SE). CASTMO, Gunnar (SE/SE); Björnåsgatan 5, S-426 53 Västra Frölunda (SE).</p> <p>(74) Agents: BERG, S., A. et al.; Albihns Patentbyrå Stockholm AB, P.O. Box 5581, S-114 85 Stockholm (SE).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>
<p>(54) Title: ABSORBENT PRODUCT WITH ARCUATE LONGSIDES OF END PORTION</p> <p>(57) Abstract</p> <p>Absorbent product (1), such as a sanitary towel, incontinence protection or protection for briefs, which product has an essentially elongate shape with a longitudinal direction (8) and a transverse direction (9), an upper side (10) and a lower side (11), and has a first end portion (6) intended to face forwards on the wearer and a second end portion (7) intended to face backwards on the wearer, which product is characterized in that the width of the second end portion (7) of the product is 40 mm maximum, and in that the long sides (2, 3) of this end portion (7) are essentially arcuate.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 00/30585

- 1 -

PCT/SE99/02086

ABSORBENT PRODUCT WITH ARCUATE LONGSIDES OF END PORTION**5 Field of technology**

Absorbent product such as a sanitary towel, incontinence protection or protection for briefs, which product has an essentially elongate shape with a longitudinal direction and a transverse direction, an upper side and a lower side, and has a first end portion intended to face forwards on the wearer and a second
10 end portion intended to face backwards on the wearer.

Background

Conventional absorbent products of the above-mentioned types usually have a rectangular or hour-glass appearance.

15

One problem associated with these shapes of absorbent product is the increasing use of string briefs. A product of rectangular or hour-glass form will protrude beyond the edges of the string briefs and spoil somewhat the elegance which is the whole point of wearing this type of underwear. The alternative is to make the
20 product sufficiently narrow so that the entire product width will be contained within the confines of the narrowest part of the string briefs. The absorption capacity of a product made in this way will however be very limited.

It has therefore been proposed to design the absorbent products with a narrower
25 part and a wider part. See for example US 5 713 886, US 5 729 835 and WO 97/39713.

WO97/39713 describes a sanitary towel with one end having a tapered three-dimensional form, and a second plane end with a straight form. One problem
30 connected with the sanitary towel described in WO97/39713 is that no guidance

WO 00/30585

PCT/SE99/02086

- 2 -

is provided as to the dimensions required to make this a discreet product.

Another problem with a product according to WO97/39713 is that the absorbent product has an end with straight form, which is also unsatisfactory from the
5 discretion point of view.

Object of the invention

The object of the invention is to overcome the above-mentioned problem and make an absorbent product which will be discreet even when used with string
10 briefs.

Short description of the invention

A product of the type described in the introduction, with which the problem associated with previously known similar products has been for the most part
15 avoided, is according to the invention characterized in that the width of the second end portion of the product is 40 mm maximum, and in that the long sides of this end portion are essentially arcuate.

According to a preferred embodiment, the width of the second end portion is
20 between 15 and 40 mm. According to another preferred embodiment, the width of the second end portion is 18-30 mm.

To be suitable for use with string briefs with open-work front, the product length is advantageously 150 mm or less.
25

Description of the invention

According to the invention, the above-mentioned problem will be solved by making the absorbent product with one portion so arranged that the product will not be visible from the outside when used with a pair of string briefs.
30

WO 00/30585

- 3 -

PCT/SE99/02086

Surprisingly it has been shown that the crutch width is fairly similar on most string briefs. Measurements show that a product width not exceeding 40 mm is sufficiently narrow to be concealed by the briefs.

5

The width will preferably lie between 15 and 40 mm.

As mentioned earlier, the absorption capacity would not normally be sufficient in the case of a product with such small width, where the width does not vary. It is therefore important for the absorbent product to follow the edge of the briefs so that the available absorption surface will be as large as possible.

10

A product which is as wide as possible is also important from the leakage point of view. The risk of leakage from the side of the briefs, as well as soiling of the briefs, is reduced if the product shape follows that of the briefs. The absorbent product according to the invention therefore has, at least in part, arcuate long sides which follow the shape of the briefs in the crutch area. The long sides of the product do not need to have a smooth arc shape, but it is sufficient that the long sides be essentially arcuate. When we say that the long sides should be essentially arcuate, they could for example also be undulated but where the undulations essentially follow an arc. Other forms for the long sides of the product are of course also possible as long as the longitudinal side edges of the product have essentially arc shape.

15

20

Studies of the crutch section of string briefs show that certain designs of the arc shape on the long sides of the product are particularly favourable. This favourable shape can be expressed in that the radius of curvature of an imagined circle which includes one of the long sides of the product lies within certain determined values. This assumes that the arc can be inscribed in a circle, but a suitable arc shape could also be inscribed in an ellipse. One way of

30

WO 00/30585

PCT/SE99/02086

- 4 -

specifying a suitable art shape, which would be valid irrespective of which geometrical figure could incorporate the arc, is to express an angle formed by virtue of the long side of the product being curved. The angle is calculated as

5 that formed by a line running in the transverse direction and tangent to the shortest short side of the product, and a line which intersects or touches one of the long sides of the product at the points where the arc either changes direction or turns into a short side. The value of the angle so formed should lie within certain predetermined limits. The most favourable angle lies between 95° and

10 110° ; see below for a detailed description of the measurement method.

It has been found that it is not necessary for the whole product to be of a determined, very narrow width since the front part of most string briefs on the market is wide enough to accommodate a product of normal width with the long

15 sides of fairly arbitrary shape. This means then that the part of the product which is worn at the front can be designed more freely, according to the absorption capacity requirements which may exist.

It follows then that only one of the end portions - that portion worn at the rear

20 and fitting into the narrow part of the string briefs - needs to be made with a maximum width and a special contour on the long sides. This part lengthwise in the product is referred to below as the rear or second end portion. That part lengthwise in the product which can be designed with a greater degree of freedom will be referred to as the front or first end portion. The two end portions

25 do not necessarily split the product into two parts of equal length. The first end portion is suitably 60 - 170 mm long, whilst the second end portion is suitably 30 - 90 mm long. The complete length of the product lies between 140 and 260 mm.

WO 00/30585

- 5 -

PCT/SE99/02086

Short description of the figures

The invention will be described below in more detail with reference to the exemplary embodiments shown on the drawings.

5

Fig. 1 shows a plan view of a sanitary towel according to the invention.

Fig. 2 shows a section along line II-II through the sanitary towel in Fig. 1.

Fig. 3 shows a plan view of protection for briefs according to the invention.

Fig. 4 shows a section along line IV-IV through the protection for briefs in Fig.

10 3.

Fig. 5 shows protection for briefs according to an alternative embodiment of the invention, viewed from below.

Fig. 6 shows a part of a product for protection of briefs according to an alternative embodiment of the invention.

15 Fig. 7 shows how the extent of the curvature on the long sides of the product can be indicated.

Detailed description of figures and embodiments

20 Fig. 1 and 2 show a sanitary towel 1 according to one embodiment of the invention.

Sanitary towel 1 has a basically elongate shape with a longitudinal direction and a transverse direction. It has two long sides 2 and 3, two short sides 4 and 5, a first 6 and a second 7 end portion, a longitudinal centre line 8 extending over the product length and a transverse centre line 9 running laterally over the product width. The longitudinal centre line is considered to be a line extending in the longitudinal direction of the sanitary towel equidistant from the long sides of the product. In the same way, the transverse centre line is a line arranged in the transverse direction of the towel, equidistant between the short sides of the

WO 00/30585

PCT/SE99/02086

- 6 -

towel. Towel 1 has an upper side 10, intended to be turned towards the wearer during use, and a lower side 11 to be turned away from the wearer during use.

- 5 Sanitary towel 1 incorporates a liquid-permeable outer layer 12 fixed on the side of the product to be turned towards the wearer (upper side 10) during use, and an impermeable rear layer 13 on the side of the towel which will be turned away from the wearer (lower side 11) during use. Between the outer layer 12 and the impermeable rear layer 13 is an absorption body 14. The outer layer and the rear
10 layer are connected at a joint outside the absorption body.

Fig. 2 shows a section through the towel 1 in Fig. 1 along line II-II. On the lower side 11 of the towel, on its impermeable layer 13, are placed the fasteners in the form of strips 15 made of pressure-sensitive adhesive arranged parallel with the
15 longitudinal centre line 8 of the towel. A removable protective layer 16 is laid on top of adhesive 15. Protective layer 16 is removed by the wearer before the towel is placed in the underwear. Other fastening methods can of course be used, such as Velcro® or friction-fastening.

- 20 Outer material 12 could be of any conventional material, for example non-woven, perforated plastic film or a laminate of these two materials.

The most suitable material for the absorption body 14 is cellulose pulp. This can be made available as rolls, bales or sheets which, for the production of sanitary
25 towels, are dry-defibred and converted in fluffed form to a pulp matting, sometimes with an admixture of "superabsorbents" which are polymers with the power to absorb several times their own weight of water or body fluids. One alternative to this is to dry-form pulp matting as described in WO 94/10956. Examples of other usable absorption materials are various types of natural fibre
30 such as cotton fibre, peat or similar. It is of course possible to use absorbent

WO 00/30585

PCT/SE99/02086

- 7 -

synthetic fibres, or mixtures of natural and synthetic fibres. Absorption body 14 can also include other materials such as form stabilizers, fluid-spreading means, or binders such as thermoplastic fibres which have been heat-treated to combine
5 short fibres and particles into a continuous material. Various types of absorbent foam material can also be used in the absorption body.

The impermeable layer 13 (rear layer) consists of a liquid-impermeable material. Thin, fluid-tight plastic films are suitable for this purpose, but it is also possible
10 to use material which is naturally permeable, but which is provided with a coating of plastic, resin or other fluid-tight material. In this way leakage of fluid from the lower side of the absorbent product is prevented. The impermeable layer 13 can therefore be made of any material which fulfills the impermeability criterion and offers sufficient flexibility and skin tolerance for this purpose.
15 Examples of material suitable for use as an impermeable layer are plastic films, non-woven and laminates of these two. Plastic films can for instance be of polyethylene, polypropylene or polyester. The impermeable layer can alternatively consist of a laminate of an impermeable plastic layer, turned towards the absorption body, and a non-woven layer turned towards the
20 underwear of the wearer. This type of construction provides a leakage-safe barrier layer with textile feel.

Between the outer layer 12 and the absorption body 14 is an acquisition layer 17. The purpose of this layer 17 is to draw fluid into the towel and transmit it
25 down to absorption body 14. This acquisition layer 17 can for example be a non-woven material of low density.

It can be seen from Fig. 1 that the long sides 2 and 3 of the sanitary towel are essentially arcuate. The arc shape is designed so that these long sides 2, 3 curve
30 inwards towards the longitudinal centre line 8. The first end portion 6 has a

WO 00/30585

- 8 -

PCT/SE99/02086

width of 65 mm at its widest part. The widest part of the second end portion 7 is 30 mm.

- 5 Fig. 3 and 4 show a product 18 for protection of briefs according to one embodiment of the invention. There is an outer layer 12, a barrier layer 13 and an absorption body 14. The absorption body can be an "airlaid", i.e. an airlaid cellulose body. The outer layer 12 and barrier layer 13 can be constructed of the same material as described for the same layers 12 and 13 of the sanitary towel
10 shown in Fig. 1 - 2.

Fig. 4 shows a section along line IV-IV through the protection for briefs in Fig. 3. On the lower side 11 of this product, on its impermeable layer 13, is a fastener in the form of a layer 15', of pressure-sensitive adhesive covering the
15 whole surface. Over this adhesive layer 15', is a removable protective layer 16 which will be removed by the wearer before the product is placed in the underwear. Other fixing methods such as Velcro® or friction-fastening can of course be used.

- 20 It can be seen from Fig. 3 that the outer contour of the protection for briefs is similar to that of the sanitary towel 1 shown in Fig. 1. The first end portion 6 has a maximum width of 60 mm, whilst the maximum width of the second end portion 7 is 22 mm.

- 25 Fig. 5 shows a product for protection of briefs according to an alternative embodiment of the invention. What distinguishes this product from that described in Fig. 3-4 is that the pressure-sensitive adhesive is applied in a different way and that the liquid-impermeable rear layer 13 can breathe. Such a breathable rear layer 13 can be SMS (spunbond-meltblown-spunbond) or a

WO 00/30585

- 9 -

PCT/SE99/02086

breathable plastic film consisting of, for example, polyethylene. This type of breathable film is described in, for example, EP 283 200. In order to retain its breathable quality when applied on a product, the lower side 11 may not be covered completely by the adhesive layer. The adhesive is therefore applied in three areas 15a, 15b and 15c. Strip 15a is laid along the longitudinal centre line 8 of the product and extends from the narrowest short side 5 over the whole length of the product. Adhesive strips 15b and 15c are arranged parallel with adhesive strip 15a, on each side of the longitudinal centre line 8, at a distance from the long sides in the first end portion 6. The adhesive strips 15a, 15b and 15c are about 10 mm wide positioned about 11 mm apart. Strip 15a is placed about 6 mm from each of the long sides 2 and 3. This is to provide more comfort for the wearer by reducing the risk of the adhesive sticking to the body hair. Strips 15b and 15c lie within the first, front end portion 6 of the product. Where the product is at its widest, the adhesive strips 15b, 15c do not reach as far as the side edges 2, 3 of the product, which they do where the product narrows closer to its transverse centre line 9.

Fig. 6 shows an alternative embodiment of the protection for briefs where the long sides 2 and 3 have an undulated form, but are essentially arcuate.

Fig. 7 shows a part of an absorbent product according to the invention. The figure shows how it is possible to specify a favorable arc shape of the long sides 2 and 3 of the product in the second end portion 7. A line X running in the transverse direction of the article is drawn at a tangent to the short side 5 situated in the second end portion of the product. At a distance $L = 80$ mm from line X, a line B is drawn parallel with X. It is those parts of the product lying between lines X and B which form basis for the measurement of the arc shape. Long side 2 intersects line B at point P. Side 2 stops curving away from longitudinal centre line 8 when it approaches the second short side 5. When it is very close thereto,

WO 00/30585

PCT/SE99/02086

- 10 -

e.g. less than a few millimetres, it curves towards longitudinal centre line 8.

That point where the curvature changes direction is called Q. A line N is then drawn between points P and Q. The angle formed between lines X and N is

5 called angle v . For a favorable curvature of long sides 2 and 3, $v = 95-110^\circ$

The long side does not need to change curvature, but can run with the same direction of curvature down to its intersection with short side 5. This intersection then forms point Q. Short side 5 can be completely straight, and line X will then

10 coincide with the short side.

The invention is not to be considered as being limited to the above-mentioned embodiments. They are intended only to clarify the invention.

15 Characteristics of various embodiments can be combined with one another within the scope of the invention. For example, the various adhesive patterns in the different embodiments can of course be combined with other alternative features of the other embodiments.

WO 00/30585

- 11 -

PCT/SE99/02086

Claims

1. Absorbent product such as a sanitary towel, incontinence protection
5 or protection for briefs, which product (1; 18) has an essentially elongate shape
with a longitudinal direction (8) and a transverse direction (9), an upper side
(10) and a lower side (11), and has a first end portion (6) intended to face
forwards on the wearer and a second end portion (7) intended to face backwards
on the wearer, characterized in that the width of the second end portion (7) of
10 the product is 40 mm maximum, and in that the long sides (2, 3) of this end
portion (7) are essentially arcuate.
2. Absorbent product according to Claim 1, characterized in that the
width of the second end portion (7) is 20-40 mm.
- 15 3. Absorbent product according to Claim 1, characterized in that the
width of the second end portion (7) is 20-30 mm.
4. Absorbent product according to any one of Claims 1-3, characterized
20 in that the angle (ν) between an end line (X), which runs in the transverse
direction of the product and tangent to the edge (5) of its second end portion (7),
and a side line (N), drawn between a first point (P), which forms the intersection
between one long side (2) of the product and a straight line (B) running in the
transverse direction of the product at a distance of 80 mm from said end line
25 (X), and a second point (Q) at the point where the curvature of said long side (2)
changes direction near said end edge (5) or with unchanged curvature direction
intersects end edge (5), lies between 95° and 110°.
5. Absorbent product according to any one of the preceding claims,
30 characterized in that the length of the product (1; 18) is 150 mm or smaller.

WO 00/30585

PCT/SE99/02086

- 12 -

6. Absorbent product according to any one of Claims 1-5, characterized in that the lower side (11) of the product is fitted with fastening means (15'; 15a, 15b, 15c), which extend in a strip-shaped manner in the longitudinal direction of the product parallel with its longitudinal centre line (8).

7. Absorbent product according to Claim 6, characterized in that the product has three fastening strips, comprising a central fastening strip (15a), which extends along the longitudinal centre line (8) over essentially the entire length of the product, and two further fastening strips (15b, 15c) which are arranged one on each side thereof and at a distance therefrom and the extent of which lies within the first, front end portion (6) of the product.

WO 00/30585

PCT/SE99/02086




FIG. 1




FIG. 3




FIG. 2







FIG. 4

WO 00/30585

PCT/SE99/02086



1

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 99/02086

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61F 13/45

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9739713 A1 (DARBY, KAMELA, J), 30 October 1997 (30.10.97), page 3, line 32 - page 4, line 2; page 5, line 24 - line 26; page 5, line 32 - page 6, line 2; page 7, line 28 - page 8, line 6; page 9, line 11 - line 16 --	1-5
Y	US 4806411 A (MATTINGLY, III ET AL), 21 February 1989 (21.02.89) --	6-7
A	US 5729835 A (WILLIAMS), 24 March 1998 (24.03.98) --	1-7
A	US 5713886 A (STURINO), 3 February 1998 (03.02.98) --	1-7

☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

- * Special categories of cited documents
- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed
- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
29 February 2000	10-03-2000
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86	Authorized officer Tomas Gustafsson/Els Telephone No. +46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

2

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 99/02086

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
T	DE 29903391 U1 (DROSE, GRIT), 24 June 1999 (24.06.99) -- -----	1-7

Form PCT/ISA/210 (continuation of second sheet) (July 1993)

INTERNATIONAL SEARCH REPORT
 Information on patent family members

02/12/99

International application No.

PCT/SE 99/02086

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9739713 A1	30/10/97	AU 2680697 A	12/11/97
		CA 2252381 A	30/10/97
		EP 0920292 A	09/06/99
		US 5683373 A	04/11/97
<hr/>			
US 4806411 A	21/02/89	AT 137661 T	15/05/96
		AU 605760 B	24/01/91
		AU 7002787 A	17/09/87
		BR 8701166 A	05/01/88
		CA 1288923 A	17/09/91
		DE 3751799 D,T	02/01/97
		EP 0237990 A,B	23/09/87
		GR 870421 A	20/07/87
		JP 2543356 B	16/10/96
		JP 62270154 A	24/11/87
		MX 169422 B	05/07/93
		PH 24838 A	30/10/90
		PH 25806 A	05/11/91
		PT 84476 A,B	01/04/87
		US 4690679 A	01/09/87
<hr/>			
US 5729835 A	24/03/98	NONE	
<hr/>			
US 5713886 A	03/02/98	NONE	
<hr/>			
DE 29903391 U1	24/06/99	NONE	
<hr/>			

Form PCT/ISA/210 (patent family annex) (July 1992)